



## *Waterproof Bucket Seat Cover Care & Use Guide*

Congratulations on the purchase of your new Solvit Products Bucket Seat Cover. This cover is designed to fit all automotive bucket seats.

**INSTALLATION:** The cover is held in place by means of five elastic straps on the back: two which hold the headrest portion in place and three which hold the cover to the bucket seatback. There is also a sewn in elastic strap which runs around the perimeter of the seat portion.



To install, first slide the “middle” three elastic straps over the top of the seat and pull the cover down so it is correctly positioned on the seat back. Slip the headrest portion of the cover, with the “top” two straps, over the seat headrest. Reposition these straps as needed to evenly distribute them.

Next, locate the Sta-put™ device on the underside of the seat cover. This consists of a short piece of plastic tubing attached to the cover by a short strap. Push the tube into the crevice where the seat back meets the seat bottom cushion. The Sta-put can be removed with a strong tug, but will hold firmly enough to keep the cover in place under normal use. Finish installation by stretching the bottom portion of the seat cover down over the seat.



**Cleaning:** Promptly wipe up any foreign matter or standing liquid with a damp cloth or sponge. For machine washing: Machine wash the cover in a commercial size front loading washing machine. Use cold water with a mild detergent. Line dry.

**CAUTION:** Always make sure the vehicle seat is dry before installing the Seat Cover.

**Warranty:** The Bucket Seat Cover is covered by a limited lifetime warranty to be free from defects in materials or workmanship. A copy of the original sales receipt is required for warranty issues.

SOLVIT Products is dedicated to offering innovative solutions to improve pets' quality of life. Please feel free to contact us with any questions, comments, or warranty issues. Thank you for your purchase!

(This document available in color on our website)